

# HOT FEED

Information on New Products from Cole Hersee Company

## Door Jamb Switch with Boot

*Can be used in a variety of momentary applications where a small switch is required. Black rubber boot covers and protects the face of the switch.*

**SPST Normally closed: Off with plunger depressed, spring return to On. 4A at 12V DC lamp load. Two brass terminals.**



**9006**  
Door Jamb Switch

### Specifications

- Operating force to move plunger:  $1.5 \pm 0.7$  kgf ( $14.71N \pm 6.86N$ )
- Endurance: 100,000 cycles at 5-15 cpm with 14V, 4A load
- Dust-Resistant
- Operating temperature:  $-30^{\circ}C$  to  $+85^{\circ}C$
- Terminal size: 2 mm x 5 mm

### ALSO AVAILABLE

from our range of Door Jamb Switches and Alarms



#### Door Jamb Switch 9001

Normally closed: Off with plunger depressed. Plated steel case, two screw terminals. Screw plate mounting.



#### Door Jamb Switch 9075

Normally closed: Off with plunger depressed. Molded plastic body and plunger. Two female bullet terminals. Snap-in installation.



#### Pilot Lights

A full range of pilot lights to alert the driver to a 'door ajar' condition.



#### Buzzer/Dual Alarm 4112-RC

Audibly and visibly alerts the driver. Long-lasting LED light.



#### Universal Buzzer 4099

Impact resistant ABS case. 12V DC. Two screw terminals with lockwashers.



#### Dual Rate Alarm 40212

90dB solid state alarm. Connects to two sensors, and operator can readily distinguish between sound emitted at 60 or 120 cycles/min. Connects to Cole Hersee sealed beam connectors or Packard 12033871.



## Cole Hersee Co.

20 Old Colony Avenue, Boston, MA USA 02127-2467 • (617) 268-2100 • Fax (617) 268-9490

See our interactive product catalog at [www.colehersee.com](http://www.colehersee.com)

All specifications and information is subject to change without notice.